

# SCANLUX



## SL215

### 21.5" Selfservice Kiosk

# Compact, Fast and Attractive

#### Versions

**SL215-WD** (WINDOWS DESKTOP STAND)

**SL215-WF** (WINDOWS FLOOR STAND)

**SL215-AD** (ANDROID DESKTOP STAND)

**SL215-AF** (ANDROID FLOOR STAND)

[www.scanlux.tech](http://www.scanlux.tech)

# SL215

## SPECIFICATION

### SL215-W Windows or Linux OS

### SL215-A Android OS



<b>Processors</b>	Intel J6412 (i3/i5/i7 optional)	RK3288(RK3568/RK3399 optional)
<b>Momory</b>	DDR3 4GB(DDR4 8GB/16GB Optional)	2GB RAM (4GB/8GB Optional)
<b>Storage</b>	MSATA 64GB (128GB/256GB/512GB Optional)	MSATA 16GB (32GB/64GB/128GB Optional)
<b>Operating Systems</b>	Windows 7/10/11 & Linux Ubuntu/CentOS	Android 7.1/Android 9.0/Android 11.0
<b>Ethernet (Audio)</b>	Realtek 8103EL 10/100M Support diskless boot	Realtek 8103EL 10/100M Support diskless boot
<b>Screen Size</b>	21.5inch LCD screen with touch	21.5inch LCD screen with touch
<b>Resolution</b>	1920*1080	1920*1080
<b>Brightness</b>	260cd/m2	260cd/m2
<b>Touch Screen</b>	True flat capacitive touch screen, multi-touch	True flat capacitive touch screen, multi-touch
<b>RJ11</b>	1	1
<b>USB 2.0</b>	5	5
<b>LAN</b>	1×Gigabit Ethernet ,RJ 45	1×Gigabit Ethernet ,RJ 45
<b>SIM card slot</b>	1 (Optional)	1 (Optional)
<b>Micro-SD</b>	None	1
<b>Serial zz(COM)</b>	Standard configuration none (2 Optional)	Standard configuration none (2 Optional)
<b>Power DC-IN</b>	1	1
<b>Power Supply</b>	Adaptor 12V/5A	Adaptor 12V/5A
<b>Printer</b>	80mm thermal receipt printer with Auto cutter	80mm thermal receipt printer with Auto cutter
<b>Scanner</b>	Barcode and QR Scanner	Barcode and QR Scanner
<b>Speaker</b>	Built-in 4Ω 3W high-fidelity speaker	Built-in 4Ω 3W high-fidelity speaker
<b>Wifi</b>	802.11a/b/g/n	802.11a/b/g/n
<b>Bluetooth</b>	Standard configuration none(Optional)	Bluetooth 4.0
<b>Operating Temperature</b>	0 °C ~ 40 °C at 20% to 90% Humidity	0 °C ~ 40 °C at 20% to 90% Humidity
<b>Storage Temperature</b>	-20 °C ~ 70 °C at 10% to 90% Humidity	-20 °C ~ 70 °C at 10% to 90% Humidity
<b>Packing</b>	Desktop: 450×410×830(mm) Floor standing: 880×230×180(mm)	Desktop: 450×410×830(mm) Floor standing: 880×230×180(mm)
<b>Packing Weight</b>	Desktop: 16.8KG Floor standing: 10KG	Desktop: 16.8KG Floor standing: 10KG
<b>Certification</b>	CE,FCC,RoHS,UKCA	CE,FCC,RoHS,UKCA
<b>Housing</b>	Metal	Metal
<b>Optional function</b>	NFC/i-button/fingerprint/credit card machine	NFC/i-button/fingerprint/credit card machine
<b>Color</b>	Black, Grey, or Custom	Black, Grey, or Custom


## Accessories

- Included**
- 1.8 mt Power Supply Cable
  - Pin pad Holder
  - Printer Keys
  - Enclosure Keys
- Optional**
- IC/ID/RFID/NFC Card Reader
  - Fingerprint Reader
  - HD Webcam
  - Regular Floor Stand

## Highlights



**Full HD 1080p  
10 points PCAP  
TouchScreen**



**Multi-Interface I/O  
USB / RS232  
BT / Wifi**



**High  
Performance  
1d + 2d  
Scanner**

**SCANLUX**

**CE FCC**



© 2024 Scanlux Electronics. Made in China.

All trademarks are the property of their respective owners. Intel, Celeron, Core are registered trademarks of Intel Corporation in the United States and other countries. Microsoft, Windows 7, Windows 8.1 and Windows 10 IoT Enterprise are registered trademarks of Microsoft Corporation in the United States and other countries. Android is a registered trademark of Google in the United States and other countries. SCANLUX shall not be liable for technical or editorial errors or omission contained herein. The information in this publication is informational purposes only and may be altered or amended by SCANLUX. All statements regarding SCANLUX's direction and intent are subject to change or withdraw without notice. Specifications may change without prior notice.

[www.scanlux.tech](http://www.scanlux.tech)